



Installation required by a Licensed Electrician; Licensed Plumber.

WS-701 FEATURES

- 110v ETL Certified (US & Canada electrical safety)
- Steam Sauna (3KW Generator) with Aromatherapy Steam outlet
- Self Cleaning Steam Generator
- Acupuncture Body Massage Jets
- Computer Control Panel with Timer
- Rainfall Ceiling Showerhead
- Circulation Fan
- Built-In Seat
- Handheld Showerheads
- Overheat Protection
- Temperature Sensor
- Tempered Glass
- 110v Whirlpool Massage Jets (Approximately 70 gal tub)
- Manufacturer provides Two Year Warranty on parts

TECHNICAL INFORMATION

- Materials: Heavy-Duty Acrylic, Tempered Glass
- Power Supply: 110V
- Steam Ready: 2-5 MIN
- Dimensions: 65.4" x 65.4" x 86.6"



Eagle Bath Inc.
www.eaglebath.com
361 East Chilton Dr
Chandler, AZ 85225

Support@eaglebath.com
Phone: (800) 576-5011
Fax: (480) 264-3922

ELECTRICAL INFORMATION

Unit must be hardwired to 2 dedicated 110v lines with GFCI breaker

Steam Shower

- Electric Voltage - 110v, 60HZ
- Electric Current – 20a for Steam Generator

Whirlpool Bathtub

- Electrical Voltage - 110v, 60HZ
- Whirlpool Motor - 1.2 HP
- Electric Current - 20a for Whirlpool Motor

PLUMBING REQUIRMENTS

- The unit is equipped with hot and cold, metal braided inch water supply hose with national pipe thread.
- Need to install hot and cold shutoffs with -male national pipe thread (**not included**).
- Supply hoses are to connect from the faucet manifold on the unit to the shutoff valves.
- All water jet features are pre plumbed with reinforced braided flexible supply hose
- **All fixtures and fittings must be checked for tightness as they may have been loosened during transport.**
- **Note:** The flexible drain hose included with this unit is for installation into a floor drain only. Substituting the existing drain setup for a setup of the installers' choice will not void the warranty of the unit as long as there is no evidence of misuse or damage to the base. If the substitute drain system is used, a 3/8 in stub must be added to the main shower drain line to connect the steam generator's automatic flushing drainage hose.
- Please call the manufacturer for updated drain info **(800) 576-5011**

GENERAL INFORMATION

- Units come broken down in panels and are assembled with screws, nuts and bolts on site.
- Note: All shower bases need to be leveled in its final resting position (all feet must be touching the ground), mark the placement, and then pull base out and begin assembly. It is advised to have base onsite before preparing drain location.
- Access panel near jets and controls is advised

EAGLE BATH

Eagle Bath Inc.
www.eaglebath.com
361 East Chilton Dr
Chandler, AZ 85225

Support@eaglebath.com
Phone: (800) 576-5011
Fax: (480) 264-3922

- **Manufacturer reserves the right to change specs or features at anytime.
Please check to confirm details. (800) 576-5011**