

Manufacturer's Limited Warranty

Manufacturer warrants to the original residential purchaser for a period indicated on this carton from the original date of purchase, that:

- The design layer of the floor will not wear through, fade from normal sunlight or artificial lighting or stain under normal use conditions in a dry indoor residential setting.
- The floor will be free of manufacturing defects.
- The floor joints will remain secure under normal use conditions.
- The floor will resist water damage caused by normal household spills and cleaning when our recommended cleaning practices are used.

Conditions

Manufacturer's Residential Limited Warranty is made subject to the following conditions:

- The flooring must be installed in accordance with Manufacturer's installation instructions. Flooring in bathroom applications must be installed using proper techniques. This Limited Warranty does not apply if the laminate flooring has not been cleaned, maintained or cared for according to the cleaning and care instructions provided by Manufacturer.
- Manufacturer warrants its products against manufacturing defects that exist in its products prior to product installation. Flooring installed with known defects is not covered under this Limited Warranty. Installer must inspect all planks for possible, recognizable defects before and during the installation as any right to claim under warranty is invalid after planks with visible defects have been installed. Manufacturer will review warranty claims only if the planks were delivered by the authorized dealer in the original packaging.
- Surface wear or damage must not be the result of abusive conditions, misuse of the product, freight damage, modification, alteration, repair or service of the product by anyone other than the authorized Manufacturer's representative, improper care or maintenance (see care & maintenance instructions), or accidents, including but not limited to severe impact, scratching, cutting, negligence or chemical damage. Gloss reduction is not surface wear. Surface wear must be readily visible from the distance of 6 feet, measuring at least 1 square inch. Wearthrough at the edges of the flooring is excluded from this Limited Warranty.
- This Limited Warranty does **not** cover water damage caused by natural disasters, standing water (e.g. from appliance failures), excessive moisture emissions from a concrete slab (more than 3 lbs. per 1,000 sq. ft. over a 24-hour period), hydrostatic pressure, pet urine or other corrosive liquids or outside water (from snow, rain or water which enters through an open window or door, etc.)
- The flooring must be installed in a dry, climate controlled, indoor, residential environment.
- Manufacturer approved accessories and underlayment **MUST** be used to validate this Limited Warranty.
- Molding and accessories are not covered by this Limited Warranty.
- Use of a floor steam cleaner or wet mopping will damage your floor and void your Limited Warranty.
- To maintain your Limited Warranty, your laminate flooring must be acclimated, installed and maintained in a controlled area, with temperature range of 64°-86°F (18°-30°C) and humidity range of 35% to 75%.

If you have a claim:

To make a Warranty claim, contact your retailer. Proof of purchase, including the date of purchase, must be presented to make a claim. This Limited Warranty applies only to the original purchaser and is not transferable.

If you have a claim within the years indicated on the this carton following the date of purchase and your claim meets the above conditions, Manufacturer, at its option, will repair, replace, or refund the cost of the defective materials. Manufacturer will also pay reasonable labor costs to repair or replace the defective materials if a claim occurs during the first five years after installation and if the floor was professionally installed. If the product for which a claim is made is no longer available, the customer shall be able to choose from Manufacturer's current product range of equal value. Manufacturer warrants repaired or replaced products for the remainder of the original Limited Warranty period only. Manufacturer reserves the right to inspect the installed planks and to remove samples if needed for analysis. To make a claim under this Limited Warranty, contact your authorized Manufacturer's dealer within thirty (30) days following the date of discovery or detection of a warranty claim. An original proof of purchase (including the date of purchase) must be presented when requesting Warranty service. This Limited Warranty, dated April 2014, supersedes all Manufacturer warranties previously issued.

DISCLAIMER OF WARRANTY

EXCEPT FOR THE FOREGOING WARRANTY, MANUFACTURER DISCLAIMS, TO THE FULLEST EXTENT PERMITTED BY FEDERAL AND STATE LAW, ALL OTHER WARRANTIES AND GUARANTEES, WHETHER EXPRESS OR IMPLIED, INCLUDING ANY IMPLIED REPRESENTATION OR WARRANTY AS TO MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE. IN NO EVENT WILL MANUFACTURER BE LIABLE FOR CONSEQUENTIAL, INCIDENTAL, SPECIAL OR EXEMPLARY DAMAGES. (SOME STATES DO NOT ALLOW FOR THE EXCLUSION OF CONSEQUENTIAL DAMAGES, SO THIS EXCLUSION OF CONSEQUENTIAL DAMAGES MAY NOT APPLY TO YOU.) THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS AND YOU MAY HAVE OTHER RIGHTS THAT MAY VARY FROM STATE TO STATE. THE FOREGOING WARRANTY CONSTITUTES THE ENTIRE AGREEMENT OF THE PARTIES, AND NO WAIVER OR AMENDMENT SHALL BE VALID UNLESS IN WRITING AND SIGNED BY AUTHORIZED REPRESENTATIVES OF MANUFACTURER.

Effective date April 2014.

Installation

Suitable subfloors for Laminate Flooring are:

- Existing floor surfaces including hardwood floors, linoleum, resilient vinyl, PVC (plastic floor surfaces must be permanently attached to the subfloor), needle felt, (dry) ceramic flooring.
- Cement floors on all grades/elevations (maximum residual moisture 2.0 CM%). With a calcium chloride test, the maximum acceptable reading is 5.0 lbs/24 hours/1000 sq. ft.
- Anhydrite and Anhydrite tiles, Magnesium Cement (max residual moisture 0.3 CM%)
- Wood subfloor moisture 14.5% maximum
- Concrete relative humidity 70% maximum

Attention! Without a documented measurement of residual moisture content, a claim against the manufacturer for damages cannot be considered. Concrete sub-floors **must always** be covered with a 6 mil vapor barrier even if linoleum, PVC or resilient vinyl is firmly attached to the concrete.

Instalación


Contrapisos adecuados para suelos laminados de son:

- Superficies de piso existentes incluyendo pisos de madera dura, linóleo, vinilo resistente, PVC (las superficies de piso plásticas deberán estar permanentemente adheridas al contrapiso), fieltro agujado, piso de cerámica (seco).
- Pisos de cemento a todos los niveles/elevaciones (humedad residual máxima 2,0 CM%). Con una prueba de cloruro de calcio, la lectura máxima aceptable es 2,3 kg/24 horas/92,9 m².
- Anhidrita y baldosas de anhidrita, cemento de magnesio (humedad residual máx. 0,3 CM%)
- Subpiso de madera humedad 14,5% máximo
- Hormigón máximo del 70% de humedad relativa

¡Atención! Sin una medición documentada del contenido de humedad residual, no puede considerarse una demanda contra el fabricante por daños y perjuicios. Contrapisos concretos siempre deben cubrirse con una barrera de vapor 6 mil aunque linóleo, PVC o vinilo resistente está firmemente sujeta al concreto.


Proposición 65 WARNING: Drilling, sawing, sanding or machining wood products generates wood dust, a substance known to the State of California to cause cancer. Use respiratory protection or other safeguards to avoid inhaling wood dust. This product contains methanol which is known to the state of California to cause reproductive harm.

Proposition 65 ADVERTENCIA: Taladrar, aserrar, lijar o labrar productos de madera genera polvo de madera, una sustancia conocida por el estado de California como causantes de cáncer. Use protección respiratoria u otras salvaguardias para evitar inhalar el polvo de madera. Este producto contiene metanol el cual es conocido en el estado de California para causar daños al sistema reproductivo.




For Successful Installation, remember:

- Acclimate for 48 hours before installing (ie. purchase on Thursday, install on Saturday).
- Identify the tongue side and the groove side.
- The tongue side (the smaller extension without a ridge on it) goes against the beginning wall.




Install vapor barrier if subfloor is cement (6 mil polyethylene film).
Instale una barrera contra vapor si el substrato es de cemento (polietileno de 6 mil).

Always use an underlayment padding above the vapor barrier and below the laminate flooring planks. If pad is pre-attached, no additional underlayment should be used.
Siempre utilice una almohadilla como base de piso sobre la barrera de vapor y debajo de las planchas de piso de laminado. Si la almohadilla está preajada, no deberá utilizarse base de piso adicional.




Remove the tongue on the panels that abut the walls to allow room for spacers and prevent problems from spills.
Retire la lengüeta en los paneles que empalman con las paredes para dar cabida a los espaciadores y evitar problemas en caso de derrames.

Always allow for 5/16" min to 3/8" max expansion around fixed objects, and 12" length as smallest usable piece.
Siempre deje de 5/16" min a 3/8" máximo expansión alrededor de objetos fijos y 12" de longitud como mínimo utilizable.



Install planks from right to left as you face the starting wall. Lock in panels lengthwise. Stagger end-joints a minimum 12" from row to row.
Instale los tablonces de derecha a izquierda como los que se enfrentan a partir de la pared. Asegure los paneles a lo largo. Alerne las juntas terminales un mínimo de 12 pulgadas de hilera a hilera.

With lengthwise connection made, lower plank into place.
Con las conexiones hechas a lo largo, baje la plancha a su lugar.




Do not tap end joints with tapping block and hammer. Merely press the end down to lock into place.
No golpee ligeramente las juntas terminales con el bloque o el martillo. Simplemente presione el extremo hacia abajo para que calce en su lugar.

To measure and cut last piece in a row, rotate offcut section 180°, mark accordingly, cut, rotate back 180° and slot into space.
Para medir y cortar la última pieza de una hilera, rote la sección del recorte a 180°, marque debidamente, corte, rote nuevamente a 180° y colóque en el espacio.



Cut last row to size. (2-1/2" min. width). Remove plastic tongue before rip cutting planks for first and last row, break tongue to size and reinsert.
Corte la última fila al tamaño (2-1/2 pulgadas de ancho, mínimo (6,3 cm)). Retírar la lengüeta de plástico antes de cortar a lo largo siguiendo la veta para la primera y la última hilera, cortar la lengüeta a medida y reinsertar.

Ensure floor is able to "float".
Asegúrese de que el piso puede "flotar".



Clean up any excess adhesive or sealant.
Limpieza cualquier exceso de adhesivo o sellador.

Always allow for 5/16" - 3/8" expansion around fixed objects.
Siempre deje de 5/16" - 3/8" expansión alrededor de objetos fijos.

An expansion gap T-strip is required when length of planks measure 40' max and when width of planks measures 25' max. Transition strips must be placed in all doorways directly under the door when the door is closed.
Se requiere un listón en T para separación de expansión cuando el largo de las planchas mida 12,2 m máx y cuando el ancho de las planchas mida 7,6 m máx. Las tiras de transición deben colocarse en todas las puertas directamente debajo de la puerta cuando la puerta está cerrada.



Remove the top part of the profile.
Quitar la parte superior del perfil de la ranura.

Use good quality wood glue to make the connection.
Utilice pegamento para madera de buena calidad para efectuar la conexión.


Slide panel into space horizontally and slot into profile. Use these modified planks under doorframes, radiators, cabinet fronts, etc. Use the pull bar to slide the planks where needed.
Deslice el panel en el espacio horizontalmente y colóque dentro del perfil. Utilice estas planchas modificadas bajo los marcos de las puertas, radiadores, frentes de gabinetes, etc. Utilice la barra de tracción para deslizar las planchas donde sea necesario.



Remove the top part of the profile.
Quitar la parte superior del perfil de la ranura.

Use good quality wood glue to make the connection.
Utilice pegamento para madera de buena calidad para efectuar la conexión.


Slide panel into space horizontally and slot into profile. Use these modified planks under doorframes, radiators, cabinet fronts, etc. Use the pull bar to slide the planks where needed.
Deslice el panel en el espacio horizontalmente y colóque dentro del perfil. Utilice estas planchas modificadas bajo los marcos de las puertas, radiadores, frentes de gabinetes, etc. Utilice la barra de tracción para deslizar las planchas donde sea necesario.



Remove the top part of the profile.
Quitar la parte superior del perfil de la ranura.

Use good quality wood glue to make the connection.
Utilice pegamento para madera de buena calidad para efectuar la conexión.


Slide panel into space horizontally and slot into profile. Use these modified planks under doorframes, radiators, cabinet fronts, etc. Use the pull bar to slide the planks where needed.
Deslice el panel en el espacio horizontalmente y colóque dentro del perfil. Utilice estas planchas modificadas bajo los marcos de las puertas, radiadores, frentes de gabinetes, etc. Utilice la barra de tracción para deslizar las planchas donde sea necesario.



Remove the top part of the profile.
Quitar la parte superior del perfil de la ranura.

Use good quality wood glue to make the connection.
Utilice pegamento para madera de buena calidad para efectuar la conexión.

Slide panel into space horizontally and slot into profile. Use these modified planks under doorframes, radiators, cabinet fronts, etc. Use the pull bar to slide the planks where needed.
Deslice el panel en el espacio horizontalmente y colóque dentro del perfil. Utilice estas planchas modificadas bajo los marcos de las puertas, radiadores, frentes de gabinetes, etc. Utilice la barra de tracción para deslizar las planchas donde sea necesario.



Remove the top part of the profile.
Quitar la parte superior del perfil de la ranura.

Use good quality wood glue to make the connection.
Utilice pegamento para madera de buena calidad para efectuar la conexión.

Slide panel into space horizontally and slot into profile. Use these modified planks under doorframes, radiators, cabinet fronts, etc. Use the pull bar to slide the planks where needed.
Deslice el panel en el espacio horizontalmente y colóque dentro del perfil. Utilice estas planchas modificadas bajo los marcos de las puertas, radiadores, frentes de gabinetes, etc. Utilice la barra de tracción para deslizar las planchas donde sea necesario.